

**BATTERY STRAPPING TOOL FOR PLASTIC STRAP P.P.— P.E.T.
DIGITAL CONTROL — FLAT AND ROUND SURFACE**

TECHICAL DATA / APPLICATIONS :

Compact, easy to use and versatile battery strapping tool equipped by new **Li-ion Battery**. Reliable to be used in industrial medium / light applications. The tool is produced standard for strap size 10mm (3/8") up to 16mm (5/8"). One battery is provided with the tool; the battery recharger is an optional.

Package type	Flat (minimum 120mm—5") Round surface (min. diam. 700mm - 28")
Strap quality	PP / PET
Strap Width	From 10mm up to 16mm (3/8" - 5/8")
Strap thickness	From 0,5mm up to 1,0mm /0,019" - 0,0038"
Max. Tension	2300N - 506 lbs
Max. Tension speed	Around 12 mt/min - 39,33 ft/min
Joint type	Friction weld seal
Weight	Around 3,8 Kg / 8,3 lbs (battery included)
Order code Digit Smart	127.990.810

- * **Li-ion BATTERY 14.4 V—3.0 Ah**
- * **NEW SEALING LEVER**
- * **LIGHT AND SMALL**
- * **ERGONOMIC HANDLE**



NEW LITHIO IONI BATTERY

FAST CHARGER FOR NEW Li-ion BATTERY

